

Stainless design. Stellar performance. Superior value.

Project name:									
Location:									
tem #: QTY:									
Model #:									

AUC48R REFRIGERATOR

TWO DOOR UNDER-COUNTER WORK TOP REFRIGERATOR



AUC48R

- Tested to NSF Standard 7 requirements for open food storage.
- Standard with full two year parts and labor warranties and a five year compressor warranty.
- Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.

► Energy Star approved



COMMERCIAL FREEZERS & REFRIGERATORS





TWO DOOR UNDER-COUNTER WORK TOP REFRIGERATOR



Magnetic door gaskets are removable and replaceable without tools.

Exterior cabinet construction consists of full stainless steel front and sides.

Interior cabinet walls are constructed of white epoxy coated steel liner with full hi-level stainless steel coved corner floor.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.



Electronic thermostat with external digital LED display for accurate control and easy reading.

Two adjustable, heavy-duty epoxy coated wire shelves.

All units come standard with heavy- duty worktop surface.

Vaulted self closing doors that remain open at 90 degrees.

Self contained capillary tube system using environmentally friendly R600a Hydrocarbon gas.

Easy to mount plate casters (two lockable) are standard with all units.

- Tested to NSF Standard 7 requirements for open food storage.
- Standard with full two year parts and labor warranties and a five year compressor warranty.

STAINLESS STEEL DESIGN • STELLAR PERFORMANCE • SUPERIOR VALUE

Model Number	Exter Width	nal Dime Depth	ensions Height*	Doors	Epoxy Coated Shelves (horizontal)	Cubic Feet	Temperature Range	Cord Length	НР	AMPS	REF	NEMA Plug	Crate Weight
AUC48R	48.25"	30″	35.625"	2	2	10.1	33°F to 41°F	8′	3/8	3	R600a	5-15P	260Llbs

Depth with door open 90° = 52.875"

*Height includes 3" for casters

Height with worktop removed = 34.125"







