

# 6455-C

# FROZEN BEVERAGE FREEZER

Two flavor, Countertop, Gravity feed









# Most Compact & Versatile

Two flavor countertop model for frozen beverage and smoothies

#### **Fast Freeze Down**

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

## Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

#### **Low Mix Indicator**

Light turns "ON" at low mix to alert operator to add mix

### See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

#### Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator light turns ON blue under Standby mode

Perfect solution for alcoholic and non-alcoholic frozen beverages in bars, restaurants, hospitals, schools and kiosks

# **Hopper Agitators**

Maintain product consistency and prevent product separation

# **Self-closing Dispensing Valves**

Automatically prevents product overflow after dispense

## **Safety Protections**

- $\bullet \ \ \mathsf{High}\,\mathsf{pressure}\,\mathsf{switch}\,\mathsf{to}\,\mathsf{prevent}\,\mathsf{compressor}\,\mathsf{overheating}$
- Thermal overload to protect from motor overheating

### **Light Box (Optional)**

- Illuminates flavor cards to attract more business
- Changes color to indicate Low Mix and Standby

## **One-hand Operated Spinner (Optional)**


- Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time






# 6455-C

# FROZEN BEVERAGE FREEZER





# **SPECIFICATIONS**

Flavors	2
Freezing Cylinders	2 x 3.8L / 4.0qt
Mix Hoppers	2 x 8.0L / 8.5qt
Output Capacity (8oz)	240 servings/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb
Net	146 / 325
Shipping	166 / 369
Volume	0.48 CBM / 17.10 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	476 / 18.7	520/20.5
Depth	651/25.6	853/33.6
Height	950 / 37.4	1090 / 42.9

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	13	2.0
220-240/60/1	15	13	2.1
110-115/60/1	20	16	1.6

•	Aboves	specii	fications	are	subje	ct to	chang	je wit	hout	no.	tice	9

FEATURES	
Control Systems	Two, Mechanical
Refrigerated Hoppers	
Hopper Agitators	$\checkmark$
Standby Mode	
Auto Closing Dispensing Valves	$\checkmark$
Low Mix Indicator Light	
Low Mix Indicator Alarm	$\checkmark$
Standby Mode	
Standby Indicator Light	$\checkmark$
High Pressure Protection	
Thermal Overload Protection	

AVAILABLE OPTIONS	
Top Air Discharge Chute	
Spinner	
Light Box	$\checkmark$