



Model: **M7548K** Item #: \_\_\_\_\_ Date: \_\_\_\_\_  
 Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

# Gas Connector Complete Kit

Gas Connectors



## Standard Features

- For use with stationary and caster-mounted commercial kitchen equipment
- Male NPT End fittings rotate 360°
- Heavy duty stainless steel corrugated tubing for flexibility
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability
- For Indoor Use Only

## Specifications

<b>Pressure</b>	▪ 1/2 psi
<b>End Fittings</b>	▪ Carbon Steel, Chrome Plated
<b>Tubing</b>	▪ Stainless Steel 304
<b>Braiding</b>	▪ Stainless Steel 304

## Includes:

No.	Name	Description
1	Gas Connector	Designed for moveable caster-mounted kitchen equipment.
2	Quick Disconnect	Easily disconnects gas hose to move equipment for maintenance and cleaning.
3	Gas Valve	Required by code to allow manual shutoff within 6 ft. of appliance.
4	Restraining Cable Kit	Prevents hose from being pulled too far. Includes mounting hardware.
5	90° Elbows	Gives versatility during installation (qty 2 included).

Visit [krowne.com](http://krowne.com) for complete replacement parts.

Model No.	Interior Size	Length	BTU/hr
M7548K	3/4"	48"	180K

## Product Compliance

- ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances
- ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances
- ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda
- Restraining Kits are required by law for all moveable gas equipment

**WARNING:** Restraining Kits are required by law for all moveable gas equipment  
 California Proposition 65 Warning

